



## 两面六面真空整形包装机

Two-sided six-sided vacuum shaping packaging machine

1、采用高清触摸屏，人机一体化，适用于粮食 、 猫砂 、 宠物料等领域的颗粒物料真空包装。

1. It adopts high-definition touch screen and human-machine integration, which is suitable for vacuum packaging of granular materials in the fields of grain, cat litter, pet food, etc.

2、两面六面可同时操作，可分开独立操作，双触摸屏,使用更灵活,操作更便捷。

2. The two sides and six sides can be operated simultaneously, and can be operated separately and independently. The dual touch screen is more flexible to use and more convenient to operate.

3、小规格(1.25kg 以内)六面包装采用双管灌料技术，一次出两包,速度更快,效率更高。

3. The small-sized (within 1.25kg) six-sided packaging adopts double-tube filling technology, which can produce two packages at a time, with faster speed and higher efficiency.

4、采用全触摸屏和国际知名电器元件，整套设备电路线缆全部穿波纹管，电控箱 IP44 等级,设备安全性更有保障。

4. It adopts full touch screen and internationally renowned electrical components. The circuit cables of the whole set of



合肥宇成机械制造有限公司  
HEFEI YUCHENG MACHINERY CO., LTD

equipment are all worn in corrugated pipes. The electric control box is IP44 grade, and the safety of the equipment is more guaranteed.

5、采用高精度振动控制技术, 速度快, 精度更高。

5. It adopts high-precision vibration control technology, which is fast and more accurate.





名称	DCS - 10F7N
包装范围	两面：2.5-10KG 六面：0.3-5KG
包装速度	两面：260 包/小时； 六面：0.3-1.25KG，速度约 400-500 包/时； 1.25-5KG，速度约 280 包/时
精确度	$\pm 2g$
分度值	1g
电源	AC380V，三相四线制，4.5KW
耗气量	0.6Mpa, 0.36m <sup>3</sup> /MIN
计量方式	高精度电子定量秤
工作温度	-10-40℃
尺寸(mm)	长 2095 *宽 1382*高 2372



Name	DCS - 10F7N
Packing range	Two sides: 2.5-10KG
Packing speed	Six sides: 0.3-5KG
Accuracy	Two sides: 260 packs/hour;
Graduation value	Six sides: 0.3-1.25KG, speed about 400-500 packs/hour;
Power supply	1.25-5KG, speed about 280 packs/hour
Gas consumption	$\pm 2g$
Measuring method	1g
Working temperature	AC380V, three-phase four-wire, 4.5KW
Dimensions (mm)	0.6Mpa, 0.36m <sup>3</sup> /MIN